


30db-500watt, Attenuator DC-6ghz, N F/F

Coaxial fixed attenuators are suitable for situations where power level reduction or circuit matching is required. They can quantitatively absorb energy from transmission lines, expand power ranges, control power levels, and can be equipped with power meters, comprehensive testers, or spectrum analyzers to accurately measure the power or spectrum of various RF microwave transmitters. Wide working frequency

- Anti pulse, low standing wave ratio
- Flat attenuation value, high reliability
- high power

Coaxial Attenuator 500W 6GHz N-TYPE



Electrical data	Requirements	
Frequency range	DC-6GHZ	
Characteristic impedance	50Ω	
VSWR	≤1.20	
Attenuation	30db	
Input Power	500w@100°C Heat Shrink	
Environmental data	Requirements	
Temperature range	-55°C to 125°C	
Material data	Requirements	
Connector parts	Material	Plating
Body	Brass	Nickel
Pin contacts	Brass	Gold-plated
Insulators	Teflon	
Dimension	320 *320*64	

Regd Add: F36a, Street No.8, Vishwas Park, Uttam Nagar, New Delhi - 110059

Tel: +91-9716582707 , +91-8810686612

Email: info@agartel.com , sales@agartel.com

web: www.agartel.in / www.rfcableconnector.in